



AUTOMATIC PAD PRINTER SERIES BALL PAD PRINTING 全自动移印机系列-球类移印机



▲ 上料系统 Loading System



▲ 印刷系统 Printing System

产品特点 STANDARD FEATURES

- 广泛应用于体育球类、玩具球类等圆面或不规则球面的单色或多色套色印刷；
- 采用PLC加触摸屏操控，功能参数灵活设置，便于操作人员调试和管理；
- 自动提升上料及下料系统，快速准确，减少人力，提高自动化程度；
- 采用坦克带输送工作台，精密分割器驱动，运行平稳，定位精准；
- 独立胶头可任意调节行程与速度，配备自动清胶装置；
- 采用密封式油墨上墨系统，节省油墨量，干净环保；
- 配备热风烘干系统，对印刷图案进行即时烘干，防止下料时碰花图案；
- 采用精密气动元件和电磁阀，确保产品的优良品质。
- Widely used for one color or many colors printing on circular or irregular spherical surfaces such as sports balls and toy balls.
- Adopting PLC and touch screen control, flexible setting of functional parameters, easy for operators to debug and manage.
- Automatic lifting and unloading system, fast and accurate, reduces manpower, and improves automation level.
- Using a tank belt conveyor worktable, driven by a precision turning table, it runs smoothly and has precise positioning.
- The independent rubber head can adjust its stroke and speed freely, and is equipped with an automatic cleaning device.
- Adopting a sealed ink cup ink system, saving ink volume, clean and environmentally friendly.
- Equipped with a hot air drying system, it can instantly dry printed patterns to prevent them from being touched during cutting.
- Using precision pneumatic components and solenoid valves to ensure excellent product quality.

规格参数 SPECIFICATION PARAMETERS

| | | | |
|------------------------------|--------------|---------------------------|----------------------|
| 型号 / Model | HP-CAP-4 | 印刷速度 / Printing Speed | 1200~1600Pcs/hr |
| 上下行程 / Up And Down Itinerary | 0~75mm | 重量 / Weight | 580kg |
| 前后行程 / Front And Back Travel | 0~450mm | 机器尺寸 / Machine Dimensions | 1900 X 1200 X 1750mm |
| 钢板尺寸 / Steel Plate Size | 120×270×10mm | 气压 / Air Pressure | 6~8bar |
| 油墨尺寸 / Ink Cup Size | Ø110×120mm | 功率 / Power | 1.7kW |

AUTOMATIC PAD PRINTER SERIES BOTTLE CAP PAD PRINTING 全自动移印机系列-瓶盖移印机



▲ 上料系统 Loading System



▲ 印刷系统 Printing System

产品特点 STANDARD FEATURES

- 广泛应用于饮料瓶盖、矿泉水瓶盖、酒瓶盖、化妆品瓶盖等一至四色的套色或叠色印刷；
- 采用PLC加触摸屏操控，功能参数灵活设置，便于操作人员调试和管理；
- 自动提升上料及下料系统，快速准确，减少人力，提高自动化程度；
- 采用坦克带输送工作台，精密分割器驱动，运行平稳，定位精准；
- 采用弹性胶辊轮式压盖系统，不伤盖子表面，等离子除尘(或选用火焰除尘)；
- 上墨方式可选用密封式油墨或敞开式墨盘，配备自动清胶装置、无件不印刷感应；
- 采用独立的发热系统烘干印刷图案，切片式卸料同步输送带，不伤盖子；
- 采用原装进口精密气动元件和电磁阀，确保产品的优良品质。
- Widely used for one to four color overlay printing of bottle caps for various beverages, mineral water, wine, cosmetics and other products.
- Adopting PLC and touch screen control, flexible setting of functional parameters, easy for operators to debug and manage.
- Automatic lifting and unloading system, fast and accurate, reduces manpower, and improves automation level.
- Using a tank belt conveyor worktable, driven by a precision turning table, it runs smoothly and has precise positioning.
- Adopting an elastic rubber roller wheel capping system, without damaging the cover surface, plasma dust removal (or flame dust removal).
- Sealed ink cup or open tray can be selected, equipped with automatic glue cleaning device, no workpiece no printing automatic detection.
- Independent heating system drying pattern, sliced discharge synchronous conveyor belt, does not damage the lid.
- Using precision pneumatic components and solenoid valves to ensure excellent product quality.

规格参数 SPECIFICATION PARAMETERS

| | | | |
|--------------------------------|------------|---------------------------|-------------------------|
| 型号 / Model | HP-CAP-2 | 印刷速度 / Printing Speed | 8000~16000Pcs/hr |
| 瓶盖范围 / Bottle Cap Range | 28~38mm | 重量 / Weight | 680kg |
| 钢板尺寸 / Steel Plate Size | 250×100mm | 机器尺寸 / Machine Dimensions | 3100 X 1200 X 2300mm |
| 油墨尺寸 / Ink Cup Size | 82×90×12mm | 气压 / Air Pressure | 5~7bar |
| 最大印刷尺寸 / Maximum Printing Size | 120×80mm | 电源 / Power Supply | 220V/110V 50/60Hz 4.0kW |